

View Online at <https://aerobasegroup.com/nsn/5930-00-938-5988>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.296 inches

**Body Length:**

0.876 inches

**Body Width:**

0.346 inches

**Body Height:**

0.600 inches

**Case Material:**

Metal

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.078 inches

**Actuator Free Position Height:**

0.425 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

17.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 3.000 amperes inductive dc

**Test Data Document:**

19204-8434153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A053a0