NSN 5930-00-938-5988

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-938-5988
Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.296 inches
Body Length:
0.876 inches
Body Width:
0.346 inches
Body Height:
0.600 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Round
Actuator Diameter:
0.078 inches
Actuator Free Position Height:
0.425 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
17.0 ounces
Actuator Movement:
Between 0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
4.000 amperes resistive dc and 3.000 amperes inductive dc
Test Data Document:
19204-8434153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)

2 wire lead

Terminal Type And Quantity:

NSN 5930-00-938-5988

Sensitive Switch - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0