

View Online at <https://aerobasegroup.com/nsn/5930-00-938-6591>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 2.115 inches and 2.135 inches

**Body Length:**

2.500 inches

**Body Width:**

0.675 inches

**Body Height:**

1.203 inches

**Unthreaded Mounting Hole Diameter:**

0.147 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.350 inches

**Actuator Height:**

0.145 inches

**Actuator Free Position Height:**

0.145 inches

**Maximum Voltage Rating In Volts:**

600.0 ac and 230.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 7.0 ounces and 11.0 ounces

**Actuator Movement:**

Between 0.060 pretravel inches and 0.080 pretravel inches and 0.015 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

400.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0