## NSN 5930-00-938-6591



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-938-6591 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** Between 2.115 inches and 2.135 inches **Body Length:** 2.500 inches **Body Width:** 0.675 inches **Body Height:** 1.203 inches **Unthreaded Mounting Hole Diameter:** 0.147 inches

**Actuator Style:** Round **Actuator Diameter:** 0.350 inches **Actuator Height:** 0.145 inches **Actuator Free Position Height:** 0.145 inches **Maximum Voltage Rating In Volts:** 600.0 ac and 230.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:** 

4.0 ounces

**Switch Actuating Force:** 

Between 7.0 ounces and 11.0 ounces

**Actuator Movement:** 

Between 0.060 pretravel inches and 0.080 pretravel inches and 0.015 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

400.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Terminal Type And Quantity:** 

4 screw

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5930-00-938-6591

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0