## NSN 5930-00-938-7573

Push Switch - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5930-00-938-7573

Panel mounted						
Overall Length:						
4.718 inches						
Overall Height:						
1.200 inches						
Overall Width:						
0.960 inches						
Body Width:						
0.960 inches						
Body Height:						
1.200 inches						
Case Material:						
Metal						
Actuator Length:						
1.040 inches						
Actuator Style:						
Rectangular						
Actuator Height:						
0.140 inches						
Actuator Width:						
0.800 inches						
Maximum Voltage Rating In Volts:						
115.0 ac and 28.0 dc						
Mounting Surface To Terminal End Distance:						
4.578 inches						
Inclosure Type:						
Fully enclosed						
Mounting Method:						
Panel						
Nonpile-up Contact Arrangement:						
4 pole, double throw, one position momentary single switch unit						
Contact Load Current Rating At Maximum Rated Voltage:						
5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes						
inductive ac and 1.500 amperes lamp ac						
Test Data Document:						
81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification						
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain						

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

**Terminal Type And Quantity:** 5 tab, solder lug and 12 turret

81349-mil-s-22885/9 government specification

Shelf Life:

N/a

## NSN 5930-00-938-7573

Push Switch - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A053a0