NSN 5930-00-938-8567

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-938-8567

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
5.000 inches
Overall Height:
5.562 inches
Overall Width:
2.688 inches
Capillary Tube Length:
120.000 inches
Bulb Length:
3.000 inches
Bulb Diameter:
0.375 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Bracket
Contact Action Stimulus:
Increase
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab w/screw
Contact Load Current Rating:
9.6 amperes resistive load fourth voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+140.00/+215.00 actuation point degrees fahrenheit
Contact Adjustment Type:
External actuation point screw
Contact Voltage Rating In Volts:
550.0 dc at sea level third voltage
Frequency In Hertz:
60.0 single voltage

NSN 5930-00-938-8567

Thermostatic Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0