

View Online at <https://aerobasegroup.com/nsn/5930-00-939-6936>

Thread Class:

2a single mounting facility

Thread Length:

0.310 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.540 inches

Overall Height:

2.680 inches

Overall Width:

1.430 inches

First Flat Length:

0.530 inches single actuator

Flat Height:

0.200 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.530 inches single actuator

Individual Section Quantity:

4

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

4 each section periphery

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 ac at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

15.0 amperes resistive load ac at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Tap, square frame

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0