## NSN 5930-00-941-2170

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-941-2170

Body Style:	
Hole mounted	
Overall Length:	
1.990 inches	
Center To Center Distance Between Mounting Facilities Parallel To Length:	
1.000 inches	
Overall Height:	
1.395 inches	
Overall Width:	
Between 0.667 inches and 0.697 inches	
Body Length:	
1.990 inches	
Body Width:	
Between 0.677 inches and 0.697 inches	
Body Height:	
0.890 inches	
Case Material:	
Plastic	
Unthreaded Mounting Hole Diameter:	
0.140 inches	
Actuator Style:	
Round	
Actuator Diameter:	
0.094 inches	
Actuator Height:	
0.055 inches	
Actuator Free Position Height:	
0.645 inches	
Maximum Voltage Rating In Volts:	
480.0 ac and 250.0 dc	
Inclosure Type:	
Fully enclosed	
Mounting Method:	
Unthreaded hole	
Nonpile-up Contact Arrangement:	
1 pole, double throw, one position momentary single switch unit	
Switch Release Force:	

Switch Actuating Force:

22.0 ounces

10.0 ounces

## **Actuator Movement:**

Between 0.050 pretravel inches and 0.010 overtravel inches and 0.007 differential inches

## NSN 5930-00-941-2170

Sensitive Switch - Page 2 of 2



250.000 milliamperes resistive dc and 20.000 amperes resistive ac

**Terminal Type And Quantity:** 

3 screw

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0