

View Online at <https://aerobasegroup.com/nsn/5930-00-941-8094>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

3.812 inches

Overall Width:

1.250 inches

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.500 inches 1st actuator

Individual Section Quantity:

3

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Operating Temperature Range:

-25.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 2nd section front

Throw Quantity:

8 2nd section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

3 2nd section

Switch Actuator Indexing Position Quantity:

8 1st actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes 2nd section rear

Switch Actuator Positioning Increment:

60.0 degrees 2nd actuator

Detent Rotational Torque Range:

+10.000/+22.000 inch-ounces 1st actuator

Switch Actuator Stop Device Type:

Fixed stop all actuators

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Terminals and contact surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0