## NSN 5930-00-941-8192

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-941-8192

## **Body Style:**

Hole mounted

#### Hazardous Locations/environmental Protection:

Humidity resistant and salt spray resistant and shock resistant and vibration resistant

## **Overall Length:**

0.876 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

#### **Overall Height:**

0.502 inches

#### **Overall Width:**

0.346 inches

#### **Body Length:**

0.876 inches

#### Body Height:

0.346 inches

## Case Material:

Metal

## **Unthreaded Mounting Hole Diameter:**

0.088 inches

#### **Actuator Style:**

Round

#### Actuator Diameter:

0.078 inches

## **Actuator Free Position Height:**

0.425 inches

#### Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

## Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

4.0 ounces

#### Switch Actuating Force:

17.0 ounces

## **Actuator Movement:**

Between 0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

## Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 5.000 amperes resistive ac

# NSN 5930-00-941-8192

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0