## NSN 5930-00-942-4071

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-942-4071
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
9.219 inches
Overall Height:
2.813 inches
Overall Width:
2.813 inches
Shaft Length:
1.219 inches single actuator
Individual Section Quantity:
15
Longest Horizontal Distance Between Mounting Centers:
2.297 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.297 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
6 each section rear
Mounting Method:
Bracket single mounting facility and threaded hole single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
24 single mounting facility
Thread Size:
0.190 inches single mounting facility
Contact Voltage Rating In Volts:
125.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
6 single actuator
Shaft Type:
Rectangular/square, threaded hole single actuator

**Square Shaft Size:** 

0.250 inches single actuator

## **NSN 5930-00-942-4071**Rotary Switch - Page 2 of 2



Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
<b>Switch Actuator Positioning Increment:</b>
22.5 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A052b0