

View Online at <https://aerobasegroup.com/nsn/5930-00-942-4072>

**Body Style:**

Bushing mount

**Overall Length:**

0.525 inches

**Overall Height:**

1.350 inches

**Overall Width:**

0.525 inches

**Bushing Length:**

Between 0.230 inches and 0.270 inches

**Body Length:**

0.525 inches

**Body Width:**

0.525 inches

**Body Height:**

Between 0.390 inches and 0.430 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.160 inches and 0.200 inches

**Actuator Height:**

Between 0.390 inches and 0.550 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, single throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

**Test Data Document:**

81349-mil-dtl-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

UNF

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A053a0