

View Online at <https://aerobasegroup.com/nsn/5930-00-942-6688>

Inside Diameter:

0.125 inches all connections

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

5.750 inches

Overall Height:

3.875 inches

Overall Width:

5.000 inches

Unthreaded Mounting Hole Diameter:

0.204 inches

Distance Between Mounting Facility Centers:

4.750 inches

Pressure Switch Type:

Differential

Mounting Method:

Flange and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

27 all pressure connection

Contact Action Stimulus:

Decrease

Thread Size:

0.125 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

0.50 actuation point inches of water and 4.00 deactuation point inches of water and 3.50 differential point inches of water

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal all connections

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Npt all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A048b0