NSN 5930-00-943-0089

Threaded hole
Thread Size:
0.190 inches



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-943-0089 **Thread Class:** 2b **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Explosion proof **Overall Length:** 4.440 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 2.440 inches **Overall Height:** 3.795 inches **Overall Width:** 3.100 inches **Body Length:** 4.440 inches **Body Width:** 3.100 inches **Body Height:** 2.400 inches **Unthreaded Mounting Hole Diameter:** 0.138 inches **Actuator Length:** 1.562 inches **Actuator Style:** Roller arm **Actuator Free Position Height:** 1.937 inches **Actuator Roller Diameter:** 0.750 inches **Actuator Roller Width:** 0.312 inches **Actuator Adapter Style:** Roller arm **Maximum Voltage Rating In Volts:** 250.0 ac and 125.0 dc Inclosure Type: Fully enclosed **Mounting Method:**

NSN 5930-00-943-0089

Sensitive Switch - Page 2 of 2



Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Switch Actuating Force:

24.0 inch-ounces

Actuator Movement:

25.0 overtravel degrees

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 10.000 amperes resistive ac

Thread Series Designator:

Unf

Terminal Type And Quantity:

6 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0