# NSN 5930-00-943-0089

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-943-0089

Thread Class:
2b
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Overall Length:
4.440 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.440 inches
Overall Height:
3.795 inches
Overall Width:
3.100 inches
Body Length:
4.440 inches
Body Width:
3.100 inches
Body Height:
2.400 inches
Unthreaded Mounting Hole Diameter:
0.138 inches
Actuator Length:
1.562 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.937 inches
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.312 inches
Actuator Adapter Style:
Roller arm
Maximum Voltage Rating In Volts:
250.0 ac and 125.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded hole
Thread Size:
0.190 inches

# NSN 5930-00-943-0089

Sensitive Switch - Page 2 of 2



## Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

#### Switch Actuating Force:

24.0 inch-ounces

### Actuator Movement:

25.0 overtravel degrees

#### Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 10.000 amperes resistive ac

### Thread Series Designator:

Unf

### Terminal Type And Quantity:

6 quick disconnect, male

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

#### Fiig:

A053a0