## NSN 5930-00-943-2705

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-943-2705

Body Style:
Hole mounted
Overall Length:
0.781 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
0.520 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.356 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.092 inches
Actuator Style:
Rectangular
Actuator Height:
0.058 inches
Actuator Width:
0.156 inches
Actuator Free Position Height:
0.360 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
End Application:
H-46 sea knight, rh-53, ch-53a/d/e, mh-53e helicopters.
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit

1.0 ounces

**Switch Release Force:** 

## **NSN 5930-00-943-2705** Sensitive Switch - Page 2 of 2



Criticality Code Justification:
Feat
Switch Actuating Force:
Between 3.0 ounces and 5.0 ounces
Actuator Movement:
Between 0.030 pretravel inches and 0.012 overtravel inches and 0.004 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac
Special Features:
Weapon system essential
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0