

View Online at <https://aerobasegroup.com/nsn/5930-00-943-4895>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

0.940 inches

Overall Height:

2.900 inches

Overall Width:

0.730 inches

Body Length:

0.940 inches

Body Width:

0.660 inches

Actuator Length:

0.730 inches

Actuator Style:

Rectangular

Actuator Width:

0.730 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 turret and 2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0