## NSN 5930-00-943-5862

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-943-5862

Hazardous Locations/environmental Protection:

Vibration resistant

liilength:

1.250 inches

**Overall Height:** 

0.440 inches

**Overall Width:** 

0.401 inches

Mounting Slot Width:

0.125 inches

Body Length:

0.776 inches

Body Width:

0.401 inches

Body Height:

0.251 inches

Distance Between Mounting Facility Centers:

1.000 inches

Tempurature Sensing Element Type:

Internal sensor

**Mounting Method:** 

Clip and slot

Features Provided:

Hermetically sealed case

**Contact Action Stimulus:** 

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

**Terminal Type:** 

Tab, solder lug

**Contact Load Current Rating:** 

2.5 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

-20.00/+200.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

50.00 actuation point degrees fahrenheit

## NSN 5930-00-943-5862

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0