

View Online at <https://aerobasegroup.com/nsn/5930-00-943-7795>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**First Flat Length:**

0.690 inches 1st actuator

**Shaft Diameter:**

0.250 inches 1st actuator 0.125 inches 2nd actuator

**Shaft Length:**

0.750 inches 1st actuator 0.500 inches 2nd actuator

**Overall Diameter:**

1.125 inches

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

2 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level 28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

10 1st actuator

**Shaft Type:**

Round, hollowed, flatted 1st actuator round 2nd actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

36.0 degrees 1st actuator

**Contact Load Current Rating:**

1.0 amperes inductive load ac at sea level and 2.0 amperes resistive load ac at sea level 1.0 amperes inductive load dc at sea level

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0