

View Online at <https://aerobasegroup.com/nsn/5930-00-943-7795>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

First Flat Length:

0.690 inches 1st actuator

Shaft Diameter:

0.250 inches 1st actuator 0.125 inches 2nd actuator

Shaft Length:

0.750 inches 1st actuator 0.500 inches 2nd actuator

Overall Diameter:

1.125 inches

Individual Section Quantity:

1

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level 28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

10 1st actuator

Shaft Type:

Round, hollowed, flatted 1st actuator round 2nd actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

36.0 degrees 1st actuator

Contact Load Current Rating:

1.0 amperes inductive load ac at sea level and 2.0 amperes resistive load ac at sea level 1.0 amperes inductive load dc at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0