NSN 5930-00-943-8047



| Rotary Switch - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/5930-00-943-8047 |
| Thread Class: |
| 2a single mounting facility |
| Thread Length: |
| 0.250 inches single mounting facility |
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Overall Length: |
| 3.108 inches |
| Shaft Diameter: |
| 0.125 inches single actuator |
| Shaft Length: |
| 0.546 inches single actuator |
| Overall Diameter: |
| 1.570 inches |
| Nonturn Device Radius: |
| 0.500 inches at 6: 00 o'clock |
| Nonturn Device Type: |
| Pin at 6: 00 o'clock |
| Switch Contact Basic Design: |
| Nonpile-up nonsymmetrical |
| Mounting Method: |
| Threaded bushing single mounting facility |
| Features Provided: |
| Metallic inclosure |
| Thread Size: |
| 0.250 inches single mounting facility |
| Shaft Type: |
| Round w/through hole single actuator |
| Terminal Type: |
| Printed circuit |
| Contact Switching Action: |
| Breaks before makes single section rear |
| Style Designator: |
| Miniature, bushing mount |
| Thread Series Designator: |
| Unef single mounting facility |

Shelf Life:

Unit Of Measure:

Demilitarization:

No

N/a

NSN 5930-00-943-8047 Rotary Switch - Page 2 of 2



Fiig:

A052b0