

View Online at <https://aerobasegroup.com/nsn/5930-00-943-9214>

Thread Class:

2a single mounting facility

Thread Length:

0.190 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof and moisture proof

Overall Length:

0.540 inches

First Flat Length:

0.030 inches single actuator

Flat Height:

0.025 inches single actuator

Shaft Diameter:

0.100 inches single actuator

Shaft Length:

0.190 inches single actuator

Overall Diameter:

0.230 inches

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Contact Load Current Rating:

250.0 milliamperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0