

View Online at <https://aerobasegroup.com/nsn/5930-00-943-9214>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.190 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof and moisture proof

**Overall Length:**

0.540 inches

**First Flat Length:**

0.030 inches single actuator

**Flat Height:**

0.025 inches single actuator

**Shaft Diameter:**

0.100 inches single actuator

**Shaft Length:**

0.190 inches single actuator

**Overall Diameter:**

0.230 inches

**Individual Section Quantity:**

1

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

2 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Metallic inclosure

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.469 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

60.0 degrees single actuator

**Contact Load Current Rating:**

250.0 milliamperes resistive load dc at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Uns single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0