# NSN 5930-00-944-1457

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-944-1457

# Thread Class:

2a single mounting facility

# Thread Length:

0.375 inches single mounting facility

# Hazardous Locations/environmental Protection:

Dustproof

## **Overall Length:**

1.474 inches

## **Overall Height:**

1.312 inches

## **Overall Width:**

1.250 inches

## Shaft Diameter:

0.250 inches single actuator

## Shaft Length:

0.312 inches single actuator

# Nonturn Device Radius:

0.531 inches at 5: 00 o'clock

# Individual Section Quantity:

1

Nonturn Device Type:

Tab at 5: 00 o'clock

#### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

## **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

2 single actuator

#### Shaft Type:

Round single actuator

### **Terminal Type:**

Threaded stud

#### **Contact Switching Action:**

Breaks before makes single section rear

## Switch Actuator Positioning Increment:

60.0 degrees single actuator

### Switch Actuator Stop Device Type:

Fixed stop single actuator

# NSN 5930-00-944-1457

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

500.0 milliamperes resistive load ac at sea level

#### **Precious Material And Location:**

Contacts and rotors surfaces silver

**Precious Material:** 

Silver

## Style Designator:

Circular wafer, bushing mount

#### **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0