

View Online at <https://aerobasegroup.com/nsn/5930-00-944-4221>

**Body Style:**

Bushing/hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof and watertight and weatherproof

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

2.547 inches

**Actuator Roller Diameter:**

0.656 inches

**Actuator Roller Width:**

0.187 inches

**Maximum Voltage Rating In Volts:**

480.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing and unthreaded hole

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Actuating Force:**

30.0 ounces

**Actuator Movement:**

Between 0.125 pretravel inches and 0.187 overtravel inches and 0.0075 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0