

View Online at <https://aerobasegroup.com/nsn/5930-00-944-5303>

Body Style:

Bushing mounted

Overall Length:

2.375 inches

Body Diameter:

Between 0.922 inches and 0.954 inches

Bushing Length:

0.500 inches

Body Length:

Between 1.109 inches and 1.141 inches

Actuator Diameter:

Between 0.796 inches and 0.828 inches

Actuator Height:

Between 0.969 inches and 1.031 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

White single actuator

Actuator Color Sequence:

Black opaque over white

Illuminated Actuator Color Sequence:

Black opaque over white

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc

Test Data Document:

10001-2515423 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0