

View Online at <https://aerobasegroup.com/nsn/5930-00-944-5303>

**Body Style:**

Bushing mounted

**Overall Length:**

2.375 inches

**Body Diameter:**

Between 0.922 inches and 0.954 inches

**Bushing Length:**

0.500 inches

**Body Length:**

Between 1.109 inches and 1.141 inches

**Actuator Diameter:**

Between 0.796 inches and 0.828 inches

**Actuator Height:**

Between 0.969 inches and 1.031 inches

**Actuator Color:**

Black single actuator

**Illuminated Actuator Color:**

White single actuator

**Actuator Color Sequence:**

Black opaque over white

**Illuminated Actuator Color Sequence:**

Black opaque over white

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc

**Test Data Document:**

10001-2515423 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0