

View Online at <https://aerobasegroup.com/nsn/5930-00-944-6176>

Hazardous Locations/environmental Protection:

Dustproof

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

9.000 inches single actuator

Unthreaded Mounting Hole Diameter:

0.250 inches single mounting facility

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

3.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

3.000 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

11 each section rear

Mounting Method:

Base single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

11 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

10.0 milliamperes resistive load dc at sea level

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0