NSN 5930-00-944-6176

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2

Dustproof

Shaft Diameter:

0.250 inches single actuator



View Online at https://aerobasegroup.com/nsn/5930-00-944-6176

Shaft Length:
9.000 inches single actuator
Unthreaded Mounting Hole Diameter:
0.250 inches single mounting facility
Individual Section Quantity:
2
Longest Horizontal Distance Between Mounting Centers:
3.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
3.000 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
11 each section rear
Mounting Method:
Base single mounting facility
Contact Voltage Rating In Volts:
28.0 dc at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
11 single actuator
Shaft Type:
Round single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Makes before breaks each section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Contact Load Current Rating:
10.0 milliamperes resistive load dc at sea level
Shelf Life:
N/a
Unit Of Measure:

NSN 5930-00-944-6176

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0