NSN 5930-00-944-9449

Rotary Switch - Page 1 of 2

0.250 inches single mounting facility

Thread Class:

Thread Length:

2a single mounting facility



View Online at https://aerobasegroup.com/nsn/5930-00-944-9449

Hazardous Locations/environmental Protection: Explosion proof **Overall Length:** 2.375 inches **Shaft Diameter:** 0.125 inches single actuator **Shaft Length:** 0.500 inches single actuator **Overall Diameter:** 0.500 inches **Individual Section Quantity: Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 3 each section rear **Throw Quantity:** 2 each section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.250 inches single mounting facility **Contact Voltage Rating In Volts:** 250.0 ac at sea level **Switch Actuator Indexing Position Quantity:** 2 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Makes before breaks each section rear **Switch Actuator Positioning Increment:** 36.0 degrees single actuator **Switch Actuator Stop Device Type:**

Fixed stop single actuator

NSN 5930-00-944-9449

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

1.0 amperes resistive load ac at sea level

Style Designator:

Snap or line

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0