

View Online at <https://aerobasegroup.com/nsn/5930-00-945-3790>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

1.750 inches

Overall Height:

1.000 inches

Overall Width:

0.938 inches

Shaft Diameter:

0.240 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.812 inches single actuator

Nonturn Device Radius:

0.375 inches at 3:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3:00 o'clock

Operating Temperature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

5 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 lowest dc voltage rating at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

335.0 milliamperes resistive load ac at sea level and 1.6 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0