NSN 5930-00-946-1320

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-946-1320

Body Style:
Hole mounted
Overall Length:
0.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.188 inches
Overall Height:
0.480 inches
Overall Width:
0.200 inches
Body Length:
0.500 inches
Body Width:
0.200 inches
Body Height:
0.350 inches
Unthreaded Mounting Hole Diameter:
0.091 inches
Actuator Style:
Round
Actuator Diameter:
0.063 inches
Actuator Height:
0.030 inches
Actuator Free Position Height:
0.320 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc

NSN 5930-00-946-1320

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A053a0