## NSN 5930-00-946-3310

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-946-3310

## Thread Length:

0.390 inches single mounting facility

## **Hazardous Locations/environmental Protection:**

Watertight

#### **Shaft Diameter:**

0.250 inches single actuator

#### **Shaft Length:**

0.890 inches single actuator

## **Individual Section Quantity:**

3

#### **Switch Contact Basic Design:**

Nonpile-up symmetrical and nonpile-up nonsymmetrical

#### **Pole Quantity:**

1 each section front

#### **Throw Quantity:**

10 1st section rear

## **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### **Rotor Through Connection Quantity:**

1 each section

## **Switch Actuator Indexing Position Quantity:**

10 single actuator

## **Shaft Type:**

Round, slotted single actuator

#### **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Makes before breaks 2nd section rear

## **Switch Actuator Positioning Increment:**

30.0 degrees single actuator

## **Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

## **Thread Series Designator:**

Unef single mounting facility

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

# **NSN 5930-00-946-3310**Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0