

View Online at <https://aerobasegroup.com/nsn/5930-00-946-4477>

Thread Length:

0.937 inches single pressure connection

Overall Length:

3.500 inches

Overall Height:

5.562 inches

Overall Width:

2.562 inches

Body Height:

4.625 inches

Unthreaded Mounting Hole Diameter:

0.219 inches

Longest Horizontal Distance Between Mounting Centers:

1.625 inches

Intermediate Horizontal Distance Between Mounting Centers:

1.375 inches

Longest Vertical Distance Between Mounting Centers:

3.625 inches

Pressure Switch Type:

Gage

Mounting Method:

Base and unthreaded hole

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

500.00 pounds per square inch

Thread Size:

0.4375 inches single pressure connection

Mounting Facility Pattern:

Obtuse triangle

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Sensing Element Burst Pressure:

600.00 pounds per square inch

Terminal Type:

Tab w/screw

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+0.00/+250.00 actuation point pounds per square inch and +0.00/+250.00 deactuation point pounds per square inch

Contact Stimulus Rating:

180.00 actuation point pounds per square inch

Contact Voltage Rating In Volts:

600.0 ac at sea level first voltage

Pressure Connector Type:

Flared, threaded external single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0