NSN 5930-00-947-1926

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-947-1926

Thread Length:
0.375 inches single mounting facility
Overall Length:
1.438 inches
Overall Height:
1.016 inches
Overall Width:
0.953 inches
First Flat Length:
0.250 inches single actuator
Flat Height:
0.218 inches single actuator
Shaft Diameter:
0.248 inches single actuator and 0.250 inches single actuator
Shaft Length:
0.688 inches single actuator
Nonturn Device Radius:
0.375 inches at 3: 00 o'clock
Individual Section Quantity:
3
Nonturn Device Type:
Nontain Borios Typoi
Tab at 3: 00 o'clock
••
Tab at 3: 00 o'clock
Tab at 3: 00 o'clock Mounting Method:
Tab at 3: 00 o'clock Mounting Method: Threaded bushing single mounting facility
Tab at 3: 00 o'clock Mounting Method: Threaded bushing single mounting facility Thread Size:
Tab at 3: 00 o'clock Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility
Tab at 3: 00 o'clock Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Shaft Flat/slot Angular Location: 56.0 degrees from nonturn device single actuator
Tab at 3: 00 o'clock Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Shaft Flat/slot Angular Location: 56.0 degrees from nonturn device single actuator Switch Actuator Indexing Position Quantity:
Tab at 3: 00 o'clock Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Shaft Flat/slot Angular Location: 56.0 degrees from nonturn device single actuator Switch Actuator Indexing Position Quantity: 9 single actuator
Tab at 3: 00 o'clock Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Shaft Flat/slot Angular Location: 56.0 degrees from nonturn device single actuator Switch Actuator Indexing Position Quantity: 9 single actuator Shaft Type:
Tab at 3: 00 o'clock Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Shaft Flat/slot Angular Location: 56.0 degrees from nonturn device single actuator Switch Actuator Indexing Position Quantity: 9 single actuator Shaft Type: Round, flatted single actuator
Tab at 3: 00 o'clock Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Shaft Flat/slot Angular Location: 56.0 degrees from nonturn device single actuator Switch Actuator Indexing Position Quantity: 9 single actuator Shaft Type: Round, flatted single actuator Switch Actuator Stop Device Type:
Tab at 3: 00 o'clock Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Shaft Flat/slot Angular Location: 56.0 degrees from nonturn device single actuator Switch Actuator Indexing Position Quantity: 9 single actuator Shaft Type: Round, flatted single actuator Switch Actuator Stop Device Type: Fixed stop single actuator
Tab at 3: 00 o'clock Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Shaft Flat/slot Angular Location: 56.0 degrees from nonturn device single actuator Switch Actuator Indexing Position Quantity: 9 single actuator Shaft Type: Round, flatted single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Style Designator:
Tab at 3: 00 o'clock Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Shaft Flat/slot Angular Location: 56.0 degrees from nonturn device single actuator Switch Actuator Indexing Position Quantity: 9 single actuator Shaft Type: Round, flatted single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Style Designator: Circular wafer, bushing mount
Tab at 3: 00 o'clock Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Shaft Flat/slot Angular Location: 56.0 degrees from nonturn device single actuator Switch Actuator Indexing Position Quantity: 9 single actuator Shaft Type: Round, flatted single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Style Designator: Circular wafer, bushing mount Thread Series Designator:
Tab at 3: 00 o'clock Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Shaft Flat/slot Angular Location: 56.0 degrees from nonturn device single actuator Switch Actuator Indexing Position Quantity: 9 single actuator Shaft Type: Round, flatted single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Style Designator: Circular wafer, bushing mount Thread Series Designator: Unef single mounting facility
Tab at 3: 00 o'clock Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Shaft Flat/slot Angular Location: 56.0 degrees from nonturn device single actuator Switch Actuator Indexing Position Quantity: 9 single actuator Shaft Type: Round, flatted single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Style Designator: Circular wafer, bushing mount Thread Series Designator:

--

NSN 5930-00-947-1926

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0