

View Online at <https://aerobasegroup.com/nsn/5930-00-947-2382>

**Overall Length:**

3.790 inches

**Overall Height:**

1.250 inches

**Overall Width:**

2.250 inches

**Body Length:**

3.410 inches

**Unthreaded Mounting Hole Diameter:**

0.205 inches

**Longest Horizontal Distance Between Mounting Centers:**

1.500 inches

**Longest Vertical Distance Between Mounting Centers:**

0.875 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Mounting Method:**

Flange and unthreaded hole

**Features Provided:**

Tamper proof cap

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

5.0 amperes resistive load first voltage and 5.0 amperes inductive load first voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+0.00/+5000.00 actuation point pounds per square inch and +0.00/+5000.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

Internal deactuation point screw and internal actuation point screw

**Contact Stimulus Rating:**

80.00 actuation point pounds per square inch and 70.00 deactuation point pounds per square inch and 10.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Frequency In Hertz:**

400.0 first voltage

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical w/mounting lugs

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0