

View Online at <https://aerobasegroup.com/nsn/5930-00-947-2382>

Overall Length:

3.790 inches

Overall Height:

1.250 inches

Overall Width:

2.250 inches

Body Length:

3.410 inches

Unthreaded Mounting Hole Diameter:

0.205 inches

Longest Horizontal Distance Between Mounting Centers:

1.500 inches

Longest Vertical Distance Between Mounting Centers:

0.875 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Features Provided:

Tamper proof cap

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load first voltage and 5.0 amperes inductive load first voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+0.00/+5000.00 actuation point pounds per square inch and +0.00/+5000.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

80.00 actuation point pounds per square inch and 70.00 deactuation point pounds per square inch and 10.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

400.0 first voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/mounting lugs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0