NSN 5930-00-947-9497

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-947-9497

Thread Class: 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 3.750 inches **Overall Height:** 1.531 inches **Overall Width:** 1.312 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 2.375 inches single actuator **Nonturn Device Radius:** 0.531 inches at 3: 00 o'clock **Individual Section Quantity:** 2 **Nonturn Device Type:** Tab at 3: 00 o'clock **Operating Tempurature Range:** -25.0/+85.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 each section front **Throw Quantity:** 6 each section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 6 single actuator **Shaft Type:** Round, breakoff single actuator **Terminal Type:** Tab, solder lug

Contact Switching Action:
Breaks before makes each section rear

NSN 5930-00-947-9497

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0