

View Online at <https://aerobasegroup.com/nsn/5930-00-948-6030>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Weather resistant

Overall Length:

5.750 inches

Overall Height:

2.375 inches

Overall Width:

2.812 inches

Body Length:

3.000 inches

Body Height:

2.375 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

2.000 inches

Longest Horizontal Distance Between Mounting Centers:

2.718 inches

Longest Vertical Distance Between Mounting Centers:

2.718 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

3000.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

50.0 milliamperes resistive load sixth voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+85.00/+540.00 actuation point pounds per square inch and +75.00/+505.00 deactuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw and external deactuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level fourth voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0