

View Online at <https://aerobasegroup.com/nsn/5930-00-948-9042>

Body Style:

Bushing mount

Overall Length:

Between 0.765 inches and 0.795 inches

Overall Height:

1.596 inches

Overall Width:

Between 0.325 inches and 0.355 inches

Bushing Length:

Between 0.355 inches and 0.385 inches

Body Length:

Between 0.765 inches and 0.795 inches

Body Width:

0.375 inches

Actuator Style:

Round

Actuator Height:

0.555 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Mounting Surface To Terminal End Distance:

0.656 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 1.000 amperes resistive ac

Test Data Document:

46859-462-1554 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0