

View Online at <https://aerobasegroup.com/nsn/5930-00-949-1166>

Thread Class:

2a

Body Style:

Bushing mounted

Overall Length:

2.575 inches

Overall Height:

1.031 inches

Overall Width:

1.031 inches

Body Diameter:

1.031 inches

Bushing Length:

Between 0.970 inches and 1.030 inches

Body Length:

1.200 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.240 inches and 0.260 inches

Actuator Height:

Between 1.345 inches and 1.405 inches

Actuator Free Position Height:

0.375 inches

Actuator Adapter Style:

Pushbutton

Adapter Bushing Length:

Between 0.970 inches and 1.030 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

Between 96.0 ounces and 192.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Terminal Type And Quantity:

12 wire lead

Specification Data:

81349-mil-s-8805/39 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0