# NSN 5930-00-949-2315

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-949-2315

# **Thread Class:**

2a single mounting facility

# Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

1.375 inches

## **Overall Height:**

1.312 inches

## **Overall Width:**

1.188 inches

### Shaft Diameter:

0.250 inches single actuator

# Shaft Length:

0.875 inches single actuator

### **Nonturn Device Radius:**

# 0.531 inches at 3: 00 o'clock

## Individual Section Quantity:

1

# Nonturn Device Type:

Tab at 3: 00 o'clock

# **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

1 single section rear

#### **Throw Quantity:**

5 single section rear

## Mounting Method:

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

5 single actuator

## Shaft Type:

Round single actuator

# **Terminal Type:**

Tab, solder lug

# **Contact Switching Action:**

Breaks before makes single section rear

# NSN 5930-00-949-2315

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

## **Detent Rotational Torque Range:**

+1.000/+6.000 inch-pounds single actuator

# Switch Actuator Stop Device Type:

Fixed stop single actuator

# **Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

# Style Designator:

Circular wafer, bushing mount

## **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

No

# Fiig:

A052b0