## NSN 5930-00-949-2328

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-949-2328

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Weatherproof
Overall Length:
4.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.750 inches
Overall Height:
5.031 inches
Overall Width:
2.500 inches
Body Length:
2.875 inches
Body Width:
2.500 inches
Body Height:
3.812 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.938 inches
Actuator Style:
Round
Actuator Height:
2.156 inches
Actuator Position-action Relationship:
Up position maintained and down position maintained and center position maintained
Maximum Voltage Rating In Volts:
575.0 ac and 230.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 1.000 amperes resistive ac
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:

## NSN 5930-00-949-2328

Lever Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0