

View Online at <https://aerobasegroup.com/nsn/5930-00-949-3655>

**Overall Length:**

1.281 inches

**Overall Width:**

0.312 inches

**Mounting Slot Width:**

Between 0.145 inches and 0.155 inches

**Body Length:**

0.710 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.145 inches and 0.155 inches

**Distance Between Mounting Facility Centers:**

Between 0.922 inches and 0.952 inches

**End Application:**

6350-00-218-0934 indicator, subassy air launch and recovery equipment

**Temperature Sensing Element Type:**

Internal sensor

**Mounting Method:**

Flange and slot and unthreaded hole

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

2.0 amperes resistive load single voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

92.00 actuation point degrees fahrenheit and 98.00 actuation point degrees fahrenheit and 2.00 differential point degrees fahrenheit and 5.00 differential point degrees fahrenheit

**Contact Voltage Rating In Volts:**

120.0 ac at sea level single voltage

**Frequency In Hertz:**

60.0 single voltage

**Media For Which Designed:**

Liquid

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular w/bracket

**Specification Data:**

80020-319701 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0