

View Online at <https://aerobasegroup.com/nsn/5930-00-949-3655>

Overall Length:

1.281 inches

Overall Width:

0.312 inches

Mounting Slot Width:

Between 0.145 inches and 0.155 inches

Body Length:

0.710 inches

Unthreaded Mounting Hole Diameter:

Between 0.145 inches and 0.155 inches

Distance Between Mounting Facility Centers:

Between 0.922 inches and 0.952 inches

End Application:

6350-00-218-0934 indicator, subassy air launch and recovery equipment

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Flange and slot and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

92.00 actuation point degrees fahrenheit and 98.00 actuation point degrees fahrenheit and 2.00 differential point degrees fahrenheit and 5.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

120.0 ac at sea level single voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular w/bracket

Specification Data:

80020-319701 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0