

View Online at <https://aerobasegroup.com/nsn/5930-00-949-4219>

Thread Class:

2b single mounting facility

Overall Length:

3.125 inches

Overall Height:

2.250 inches

Overall Width:

2.250 inches

First Flat Length:

0.406 inches single actuator

Flat Height:

0.184 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.625 inches single actuator

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.500 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

0.750 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.750 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 each section rear

Throw Quantity:

6 each section rear

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Precious Material And Location:

Contacts and wiper arms silver

Precious Material:

Silver

Style Designator:

Circular wafer, panel mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0