

View Online at <https://aerobasegroup.com/nsn/5930-00-949-4219>

**Thread Class:**

2b single mounting facility

**Overall Length:**

3.125 inches

**Overall Height:**

2.250 inches

**Overall Width:**

2.250 inches

**First Flat Length:**

0.406 inches single actuator

**Flat Height:**

0.184 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.625 inches single actuator

**Individual Section Quantity:**

2

**Longest Horizontal Distance Between Mounting Centers:**

1.500 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:**

0.750 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

0.750 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

4 each section rear

**Throw Quantity:**

6 each section rear

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.164 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level

**Mounting Facility Pattern:**

Isosceles triangle single mounting facility

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level

**Precious Material And Location:**

Contacts and wiper arms silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, panel mount

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0