NSN 5930-00-949-6566

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-949-6566
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
0.780 inches
Overall Height:
1.760 inches
Overall Width:
0.680 inches
Bushing Length:
0.250 inches
Body Length:
0.780 inches
Body Width:
0.680 inches
Actuator Diameter:
0.323 inches
Actuator Height:
0.330 inches
Actuator Color:
Black single actuator
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac
Test Data Document:
13499-266-6815-010 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Uns

3 screw

Terminal Type And Quantity:

NSN 5930-00-949-6566

Push Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0