

View Online at <https://aerobasegroup.com/nsn/5930-00-950-9409>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.245 inches single mounting facility and 0.255 inches single mounting facility

**Width Between Flats:**

0.220 inches single actuator

**Overall Length:**

Between 3.830 inches and 4.226 inches

**Overall Height:**

Between 2.297 inches and 2.327 inches

**Overall Width:**

Between 1.953 inches and 1.983 inches

**First Flat Length:**

0.360 inches single actuator and 0.390 inches single actuator

**Shaft Diameter:**

0.247 inches single actuator and 0.250 inches single actuator

**Shaft Length:**

0.688 inches single actuator

**Individual Section Quantity:**

6

**Operating Temperature Range:**

-0.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section rear

**Throw Quantity:**

9 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

9 single actuator

**Shaft Type:**

Round, parallel flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

15.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Uns single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0