

View Online at <https://aerobasegroup.com/nsn/5930-00-951-0132>

**Thread Class:**

2b

**Body Style:**

Hole mounted

**Body Length:**

1.880 inches

**Body Width:**

Between 0.490 inches and 0.550 inches

**Body Height:**

Between 1.270 inches and 1.330 inches

**Unthreaded Mounting Hole Diameter:**

0.138 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.500 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.375 inches

**Actuator Free Position Height:**

0.375 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded hole

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

14.0 ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

0.250 amperes resistive dc and 0.100 amperes inductive dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac

**Test Data Document:**

81349-mils8805-56 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0